

SWEDOOR

Door Construction



Door Blade

- Wood fibre core sealed between high density fibreboard and 0.5mm (approx. 24SWG thickness) aluminium stabilising sheets
- Edged with rebated timber stiles and rails.
- Door Thickness 60mm.

Door Frame

- Head & jambs manufactured from selected pine fully machined, assembled and pre-drilled to accept screw fixings for installation.
- New designed double siliconised rubber compression weather strip create a continuous a seal between door and frame.
- Aluminium threshold designed specifically both for part Q & M - to meet barrier free access regulations.

Ironmongery



Hinges

- 2 heavy duty metal adjustable ball bearing hinges and machine threaded screws through frame to reinforced plates.

Lock and Cylinder

- Multiple 3 point espagnolette locking system, tested to BS3621:1980 with adjustable security striking plate fitted as standard.
- High security sash lock cases available as non standard option to meet BS3261.
- Twin cylinders available as non standard option.
- Oval single cylinder and thumb turn fitted as a standard specification.



Letterbox

- High quality letterbox assembly combining black brush strip and draught excluding flap seals, telescopic sleeve for a perfect fit and wide 12" outward opening letter flap.
- High quality chrome and brass coloured finish available.

Door Viewer

- Fitted as standard on certain door stiles – 180° angle, chrome or brass finish available.



Options

- Module sizes – Module 10 (988 x 2080mm Overall frame size) is the standard size specification due to the regulations on barrier free access, however alternative sizes are available on request.

Where Swedoor external doorsets are supplied to very exposed sites please refer to NHBC standards 6.6.7

**Architectural
Doors &
Windows
Limited**

Architectural Doors & Windows Ltd
9 South Wardpark Place
Wardpark South
Cumbernauld G67 3HX
Tel : 01236 780022 Fax : 01236 780021
Email : info@adwlimited.co.uk
Web : www.adwlimited.co.uk

SWEDOOR

Exterior Composite Doorsets



Range of Sizes
Range of Colours
Secured by Design Certified

When you need more
than an ordinary door

**Architectural
Doors &
Windows
Limited**

Secured by Design



Official Police Security Initiative



**Architectural
Doors &
Windows
Limited**

Standard Module Size is Mod 10x21, Door Blade is 925 x 2031,
Overall Frame Size is 988 x 2080mm, Frame Depth is 115mm



Repton



Barents



Roxburgh



Delta



Barents W85



Puccini



Puccini W35



Donington



Edale



Toplight



EPD
(Single)
Sidelight



EPP
(Double)
Sidelight



EPC
(Triple)
Sidelight



Puccini (Pair)



Puccini W35 (Pair)



**Architectural
Doors &
Windows
Limited**

Options

Special sizes are available up to a maximum of 1250 x 2266mm

Various double doors are available on request

Stainless steel kick plates are available as an option

Glazing

All glazed doorsets come with clear laminated glass as standard. Alternatively laminated Ice Obscure glass is available as an option, please specify when placing an order.



Outward Opening doorsets

Outward opening doorsets are available as an option
These doorsets have a 105mm frame depth

Alternative NCS Colours

5 basic Colours are available at a nominal extra cost.

An extended range of colours and dual finishes are also available as an option, please specify your requirements.

| | |
|--|-----------------|
| | NCS S 5500-N |
| | NCS S 3010-G10Y |
| | NCS S 2565-R80B |
| | NCS S 2570-Y90R |
| | NCS S 7020-R90B |



SWEDOOR